


Vertical Elevator - Full Process Solution Provider



TD Belt Vertical Elevator



TD-type bucket elevator cites the advanced technology of Corning Corporation of the United States and is an updated product of D-type bucket elevator. Its main features are: increasing specifications and hopper types, increasing the operating speed and conveying capacity of the hopper, increasing the lifting height, thereby expanding the scope of use, which can meet the transportation of various materials in building materials, machinery, chemical industry, electric power, grain, light industry and other departments Require. TD Series Bucket Elevator Applicable Scope: The bucket elevator adopts centrifugal and mixed discharge methods, and is suitable for conveying powdery, granular and small non-grinding, flat materials with an accumulation of less than 1.5t/cubic Abrasive materials. Such as grain, coal, sand, cement, fertilizer, etc.

Models of TD Belt Elevator

Customization is acceptable.

Model	Capacity	Belt width	Powder max size
TD160	5.4-16m ³ /h	200 mm	25mm
TD250	12-35 m ³ /h	300 mm	35mm
TD315	17-40 m ³ /h	400 mm	45mm
TD400	24-66 m ³ /h	500 mm	55mm
TD500	38-92 m ³ /h	600 mm	55mm
TD630	85-142 m ³ /h	700 mm	55mm




Plate Chain Elevator



Full Process Solution Provider – SDCAD

Model	Capacity	Spindle speed	Material size	Volume per Hopper
NE15	15 m3/h	15.54 rpm	<40mm	2.5 L
NE30	32 m3/h	16.45 rpm	<50mm	7.8 L
NE50	60 m3/h	16.45 rpm	<50mm	15.7 L
NE100	110 m3/h	14.13 rpm	<70mm	35 L
NE150	170 m3/h	14.13 rpm	<70mm	52.2 L
NE200	210 m3/h	10.9 rpm	<100mm	84.6 L
NE300	320 m3/h	10.9 rpm	<100mm	127.5 L
NE400	380 m3/h	8.3 rpm	<120mm	182.5 L
NE500	470 m3/h	7.1 rpm	<120mm	260.9 L
NE600	600 m3/h	7.1 rpm	<120mm	33.2 L
NE800	800 m3/h	6.2 rpm	<140mm	501.8 L


Bucket Speed 0.5m/s




SHANDONG CAD INDUSTRY MACHINERY EQUIPMENT CO. LTD

admin@cementsilo.top

Chain Elevator



Model	Capacity	Chain Dia.x Dis.	Powder max size
TH160	16 / 25 m3/h	14x50mm	20mm
TH200	18 / 29 m3/h	14x50mm	25mm
TH250	32 / 49 m3/h	14x50mm	30mm
TH315	35 / 59 m3/h	18x64mm	35mm
TH400	58 / 94 m3/h	18x64mm	40mm
TH500	73 / 118 m3/h	22x86mm	50mm
TH630	114 / 185 m3/h	22x86mm	660mm



SHANDONG CAD INDUSTRY MACHINERY EQUIPMENT CO. LTD

admin@cementsilo.top


Customized Elevator

Design, Structure, Material (Stainless Steel), inlet / outlet way /Qty. all can be customized.



SHANDONG CAD INDUSTRY MACHINERY EQUIPMENT CO. LTD


admin@cementsilo.top









SHANDONG CAD INDUSTRY MACHINERY EQUIPMENT CO. LTD

admin@cementsilo.top

Structure Show / Spart Parts







SHANDONG CAD INDUSTRY MACHINERY EQUIPMENT CO. LTD

admin@cementsilo.top